# HP Latex 630 Printer



## Embrace new possibilities with outstanding quality—easily



## POSSIBILITIES—Level up your offering

- Produce a wide range of signage and décor jobs including applications with thin film and papers.
- Deliver stunning prints with vivid colors, smooth gradients, and sharp text at 150 ft<sup>2</sup>/hr.<sup>1</sup>
- Simple finishing, lamination, and installation with flexible inks and prints that come out dry.

## EFFORTLESS—Get it done quickly and easily

- Find peace of mind with automatic maintenance processes and user-replaceable printheads.
- Save space and time with fast and automated frontloading system.
- Easily reprint projects with job storage in the printer up to 10 GB.
- Monitor your printer from anywhere and expand your capabilities with the cloud-based HP PrintOS app.

## GO BEYOND—Lead with environmental certifications<sup>2</sup>

- Contribute to a comfortable<sup>3</sup> working environment with water-based HP Latex Ink
- Differentiate your business with environmental certifications<sup>2</sup>—including UL ECOLOGO®4 and
- Reduce your plastics consumption with cartonbased cartridge<sup>6</sup> and labelless supplies; free recycling via HP Planet Partners.

## For more information, please visit https://www.hp.com/go/latex-630

## Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://lkc.hp.com/

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

<sup>1</sup> Standard mode (Generic SAV Calendar) 6-pass, 6 colors, 110% ink density. Based on internal HP testing on MACTAC JT 8500 WG-PG. Print speed may vary due to the adaptive printing mechanism, which is designed to Eased on internal competitive analysis with public information. Applicable to HP Latex technology compared to competitive large format printing alternatives using solvent and UV technologies. See individual product

data sheets for more information at http://hp.com/go/latex

Based on odor sensory evaluation when printing with the HP Latex 630 series printer and Mimaki UJV 100-160. Tests done in a 57 sqm room with 5ACH. Test conducted by Odournet following the standard VDI3882,

where the HP Latex 630 series air quality were characterized, when Printing, as "neutral" for hedonic tone compared to the Mimaki UIC 100-160.

4 UL ECOLOGO® Certified HP 832 Latex inks meet a range of stringent human health and environmental considerations. For certifications, see http://www.ul.com/EL and http://www.ul.com/gg

<sup>&</sup>lt;sup>5</sup> Applicable to select HP Latex printers. EPEAT registered where applicable/supported. See http://epeat.net for registration status by country.

<sup>6</sup> Applicable to HP 832. Plastic reduction based on moving from plastic ink cartridge to cardboard ink cartridges, with annual manufacturing saving of 33 tons of plastic based on average units of HP 831 and HP 831A ink cartridges from 2018 to 2020.

Visit http://hp.com/recycle to see how to participate and for HP Planet Partners program availability; program may not be available in your jurisdiction. Where this program is not available, and for other consumables not included in the program, consult your local waste authorities on appropriate disposa

## **Technical specifications**

Printing modes	35 m²/hr - Max Speed (2-pass) 18 m²/hr - Speed (4-pass) 14 m²/hr - Standard (6-pass) 11 m²/hr - Quality (8-pass) 8 m²/hr - High Saturation (12-pass)	
Drint recolution	7 m²/hr - Standard for Backlits and Textiles (14-pass) <sup>1</sup>	
Print resolution	Up to 1200 x 1200 dpi	
Ink types Ink cartridges	Water-based HP Latex Inks	
	8 (black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer, HP Latex Overcoat)  1 L	
Cartridge size Printheads		
Long-term print-to-print repeatability	5 (1 cyan/black, 1 magenta/yellow, 1 light cyan/light magenta, 1 HP Latex Optimizer, 1 HP Latex Overcoat) 95% of colors < 3 dE2000 <sup>2</sup>	
Media		
Handling	Roll feed, take-up reel, automatic horizontal cutter (for vinyl, banner and canvas <sup>3</sup> , paper-based media, and film)	
Media types	Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas, synthetics, (fabrics, mesh, textiles, and any other porous materials require a liner)	
Roll size	457 to 1625-mm rolls (580 to 1625-mm rolls with full support)	
Maximum roll weight	42 kg	
Maximum roll diameter	250 mm	
Thickness	Up to 0.5 mm	
Applications	Banners, Customizable clothing, Displays, Exhibition and event graphics, Exterior signage, Floor graphics, Independent posters, Interior decoration, Labels and stickers, Light boxes - film, Light boxes - paper, POP/POS, Posters, Vehicle graphics, Wall decals, Window graphics	
Connectivity		
Interfaces	Gigabit Ethernet (1000Base-T)	
Dimensions (W x D	x H)	
Printer	2603 x 844 x 1405 mm	
Shipping	2800 x 1130 x 1271 mm	
Operating area	2793 x 2100 mm	
Weight		
	230 kg	
Weight Printer Shipping	230 kg 347 kg	
Printer	-	
Printer Shipping What's in the box	347 kg  HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor	
Printer Shipping What's in the box Environmental ran	347 kg  HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor	
Printer Shipping What's in the box Environmental ran Operating temperature	347 kg  HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor	
Printer Shipping What's in the box Environmental ran Operating temperature Operating humidity	347 kg  HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C	
Printer Shipping What's in the box Environmental ran Operating temperature Operating humidity Acoustics	347 kg  HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C	
Printer Shipping What's in the box  Environmental ran Operating temperature Operating humidity  Acoustics Sound pressure	347 kg  HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, HP SAI Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C  20 to 80% RH (non-condensing)	
Printer Shipping What's in the box  Environmental ran Operating temperature Operating humidity  Acoustics Sound pressure Sound power	347 kg  HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, HP SAI Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C  20 to 80% RH (non-condensing)  55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)	
Printer Shipping What's in the box  Environmental ran Operating temperature Operating humidity Acoustics Sound pressure Sound power Power	347 kg  HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C  20 to 80% RH (non-condensing)  55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)	
Printer Shipping What's in the box  Environmental ran Operating temperature Operating humidity Acoustics Sound pressure Sound power Power	347 kg  HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C  20 to 80% RH (non-condensing)  55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)  7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep)	
Printer Shipping What's in the box  Environmental ran Operating temperature Operating humidity Acoustics Sound pressure Sound power Power Consumption	347 kg  HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C  20 to 80% RH (non-condensing)  55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)  7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep)  0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <4.5 W <sup>4</sup> (sleep) (<15 W <sup>5</sup> with DFE)  Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max	
Printer Shipping What's in the box  Environmental ran Operating temperature Operating humidity Acoustics Sound pressure Sound power Power Consumption Requirements	347 kg  HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C  20 to 80% RH (non-condensing)  55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)  7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep)  0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <4.5 W <sup>4</sup> (sleep) (<15 W <sup>5</sup> with DFE)  Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max	
Printer Shipping What's in the box  Environmental ran Operating temperature Operating humidity Acoustics Sound pressure Sound power Power Consumption Requirements Certification Safety	347 kg  HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C  20 to 80% RH (non-condensing)  55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)  7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep)  0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <4.5 W <sup>4</sup> (sleep) (<15 W <sup>5</sup> with DFE)  Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord	
Printer Shipping What's in the box  Environmental ran Operating temperature Operating humidity Acoustics Sound pressure Sound power Power Consumption Requirements  Certification	347 kg  HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, HP SAi Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C  20 to 80% RH (non-condensing)  55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)  7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep)  0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <4.5 W <sup>4</sup> (sleep) (<15 W <sup>5</sup> with DFE)  Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord  IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC)  Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and	

## **Ordering information**

### Product

HP Latex 630 Output Platen Protector Accessory
HP Latex 600/700/800 User Maintenance Kit
HP Latex Media Feed Accessory
HP Latex 630/700/800 Media Loading Accessory
Н

#### Original HP printing supplies

4UU94A	HP 836 Optimizer Latex Printhead	
4UV75A	HP 832 1-liter Black Latex Ink Cartridge	
4UV76A	HP 832 1-liter Cyan Latex Ink Cartridge	
4UV77A	HP 832 1-liter Magenta Latex Ink Cartridge	
4UV78A	HP 832 1-liter Yellow Latex Ink Cartridge	
4UV79A	HP 832 1-liter Light Cyan Latex Ink Cartridge	
4UV80A	HP 832 1-liter Light Magenta Latex Ink Cartridge	
4UV81A	HP 832 1-liter Optimizer Latex Ink Cartridge	
4UV82A	HP 832 1-liter Overcoat Latex Ink Cartridge	
4UV95A	HP 836 Black/Cyan Latex Printhead	
4UV96A	HP 836 Magenta/Yellow Latex Printhead	
4UV97A	HP 836 Light Cyan/Light Magenta Latex Printhead	
4UV98A	HP 836 Overcoat Latex Printhead	

#### Original HP large format printing materials

HP Recycled® Removable Adhesive Fabric, 3-in Core (Latex/solvent): REACH compliant?

HP Recycled® Satin Carvas, 3-in Core (Latex/solvent): REACH compliant?

HP Premium Poster Paper: FSC® certified®

HP PVC-free¹0 Wall Paper: UL GREENGUARD GOLD Certified¹1, FSC® certified®, meets AgBB criteria¹2

HP Permanent Gloss Adhesive Vinyl: REACH compliant?

HP Prime Gloss Air GP: REACH compliant?

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com

#### Service and Support

U60QHE HP 2 year Plus Service Plan Hardware Support w/DMR U60QIE HP 3 year Plus Service Plan Hardware Support w/DMR
U60QIE HP 3 year Plus Service Plan Hardware Support w/DMR
U60QIE HP 5 year Plus Service Plan Hardware Support w/DMR
U60QMPE HP 1 year Post Warranty Plus Service Plan Hardware Support w/DMR U60QNPE HP 2 year Post Warranty Plus Service Plan Hardware Support w/DMR



















 $<sup>^{1}\,</sup>Print\,speeds\,may\,vary\,due\,to\,the\,adaptive\,printing\,mechanism\,to\,avoid\,image\,quality\,defects.\,Print\,mode\,names$ may vary depending on the media or application.

The color variation between printed jobs has been measured at 12 pass mode on vinyl media. Reflective

<sup>-</sup> The cotor variation between printed jobs has been measured at 12 pass mode on vinyl media. Reflective measurements on a 943 color target under CIE standard Illuminant DSO, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above 3 dE2000. Backlit substrates measured in transmission mode may yield different results.
3 Automatic horizontal cutter is for use with thinner banners and canvas only. It is recommended to perform a test.
4 Excluding Type 2 DFE (Digital Front End) as defined in Energy Star® Product Specification for Imaging Equipment version 3.1.

<sup>&</sup>lt;sup>4</sup> Excluding Type 2 DFE (Digital Front End) as defined in Energy Star® Product Specification for Imaging Equipment version 3.1.
<sup>5</sup> Total power measured in sleep mode including the Digital Front End contained on the product.
<sup>6</sup> Product consists of PET fabric and coatings. With liner attached, 72% by weight of the product consists of recycled content. Base material fabric is made from 100% recycled resin.
<sup>7</sup> As of the date of this document, this product does not contain any of the chemicals on the EU's Candidate List for Authorization (otherwise known as Substances of Very High Concern) in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Article 33 Declaration published at HP Printing Products and Consumable Supplies.
<sup>8</sup> 62% by weight of the product consists of recycled content. Base material fabric is made from 100% recycled resin. Certified according to Global Recycled Standard (GRS) Version 3.0, March 2017.
<sup>9</sup> Trademark License code FSC-C115319.
<sup>10</sup> Chemical analysis demonstrated elemental chlorine to be below 200 ppm. Presence of chlorine is attributed to residual chlorine used in the papermaking process, and not due to the presence of PVC.
<sup>11</sup> HP PVC-free Wall Paper printed with HP Latex inks is UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL SREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit http://uc.com/gg
<sup>12</sup> With HP Latex Inks, prints meet AgBB criteria for health-related evaluation of VOC emissions. See http://unweltbundesamt.de/en/topics/health/commissions-working-groups/committee-for-health-related-evaluation-of-building