HP Latex 700 W Printer

Win high-value jobs, equipped with white ink, and sharpen your sustainability edge with HP Latex





Access white and produce the highest value jobs

- Extend your portfolio into high-margin stickers and window graphics with the whitest white.¹
- Print white without complexity—automatic recirculation and printhead cleaning reduce manual purging.
- Deliver vivid colors at high speed, get striking contrast using pure blacks, and expect sharp 4point text.
- Choose from a wide application range covering banners/textiles/poster paper, canvas, wallpaper, and vinvl

Beat your deadlines with smart, efficient printing

- Fast saturated color up to 31 m²/hr outdoor, 21 m²/hr indoor.²
- Control print operations virtually anytime, anywhere with HP PrintOS tools, and grow with HP Learn trainings
- Work fast processing reprints and multi-copy jobs with a smart front panel, and store up to 100 jobs.
- Enjoy fast and easy spindle-less loading and media access for rolls up to 55 kg.

Sharpen your sustainability edge with HP Latex

- Innovative water-based HP Latex Inks—no HAPs³, no required hazard warning labels, and odorless prints.4
- Zero landfill—local outer carton recycling, free take-back of inner ink bag/printhead, HP Planet Partners.⁵
- Choose from a wide range of compatible ecoconscious media.6
- HP Latex prints are recyclable, returnable, or nonhazardous and safe for disposal.⁷

For more information, please visit http://www.hp.com/go/latex700series

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://hplatexknowledgecenter.com/

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

¹ Whitest white based on ISO/DIS 23498 compared to competitive alternatives using solvent and UV technologies under \$50,000 USD as of May, 2020. Test performed on black opaque self-adhesive vinyl (L*4.16 - a:0.48-b:2,34) with 160% UF printmode using HP 832 1-liter

 ¹ Whites take the based on ISO/IDS 23498 compared to competitive alternatives using solvent and UV technologies under \$50,000 USD as of May, 2020. Test performed on black opaque self-adhesive vinyl (L*4.16 – a:0,48-b:2,34) with 160% UF printmode using HP 832 1-liter White Later kink carridge. Visual opacity = 91%.
 ² Outdoor mode (Banner) 4-pass, 100%. Indoor mode (SAV) 6-pass, 100%. Based on internal HP testing in 6 sptember 2020 on Avery 3001. Print speed may vary due to the adaptive printing mechanism to avoid image quality defects.
 ³ HP Late kinks were tested for Hazardous Air Pollutants, as defined in the Clean Air Act, per U.S. Environmental Protection Agency Wethod 311 (testing conducted in 2013) and none were detected.
 ⁴ There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.
 ⁵ The ink cartridge HP Eco-Carton outer carton is 100% recyclable through local cardboard/paper programs. Inner materials including the ink bag are 55% recyclable and can be returned free of charge to the HP Planet Partners program for reprocessing of plastic parts. Zero Landfill. For ink bag and printhead take back, visit http://www.hp.com/jecycle to see how to participate and for the Planet Partners program availability, program may not be available in your jurisdiction. Where this program is not available, and for other consumables not included in the program, consult your local waste authorities on appropriate disposal.
 ⁶ See http://www.hp.com/gencycle.
 ⁷ See http://www.hp.com/gencycle.
 ⁸ See http://www.hp.com/gencycle.
 ⁸ See http://www.hp.com/gencycle.
 ⁹ See http

Technical specifications

Print		
Printing modes	$ \begin{array}{l} 105 \ m^2/hr - Max Speed (1-pass) \\ 31 \ m^2/hr - High Speed (4-pass) \\ 21 \ m^2/hr - Production Fast (6-pass) \\ 17 \ m^2/hr - Production Quality, Textiles and Backlits (8-pass) \\ 16 \ m^2/hr - High Saturation (12-pass) \\ 12 \ m^2/hr - High Saturation Backlits and Textiles (14-pass) \\ 17 \ m^2/hr - White Spot (60%) \\ 9 \ m^2/hr - White Overfload (60%) \\ 9 \ m^2/hr - White Underfload (100%) \\ 2 \ m^2/hr - 3 Layers Day & Night (160%)^1 \\ \end{array} $	
Print resolution	Up to 1200 x 1200 dpi	
Ink types	Water-based HP Latex Inks	
Ink cartridges	9 (black, cyan, light cyan, light magenta, magenta, yellow, white, HP Latex Optimizer, HP Overcoat)	
Cartridge size	1L	
Printheads	10 (2 cyan/black, 2 magenta/yellow, 2 light cyan/light magenta, 2 white, 1 HP Latex Optimizer, 1 HP Overcoat)	
Long-term print-to-print repeatability	95% of colors $\leq 1.5 \text{ dE2000}^2$	
Media		
Handling	Roll feed, take-up reel, wiper roller ³ , automatic horizontal cutter (for vinyl, banner and canvas ⁴ , paper-based media, and film)	
Media types	Banners, self-adhesive vinyls, films, fabrics, papers, wall coverings, canvas, synthetics, mesh, textiles ⁵	
Roll size	254 to 1625-mm rolls (580 to 1625-mm rolls with full support)	
Roll weight	55 kg	
Roll diameter	250 mm	
Thickness	Up to 0.5 mm	
Applications	Banners; Displays; Exhibition and event graphics; Exterior signage: Indoor posters; Interior decoration; Light boxes - film; Light boxes - paper; Murals; POP/POS; Posters; Textile; Vehicle graphics; Window graphics; Stickers	
Connectivity		
Interfaces	Gigabit Ethernet (1000Base-T)	
Dimensions (w x d	x h)	
Printer	2583 x 852 x 1402 mm	
Shipping	2800 x 1130 x 1270 mm	
Operating area	2793 x 2100 mm	
Weight		
Printer	267 kg	
Shipping	368 kg	
What's in the box	HP Latex 700 W Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, setup poster, documentation software, power cords, air purgers, 2-in spindle adaptor	
Environmental ran	ges	
Operating temperature	15 to 30°C	
Operating humidity	20 to 80% RH (non-condensing)	
Acoustics		
Sound pressure	60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)	
Sound power	7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep)	
Power		
Consumption	1.5-2.6 kW (5 kW peak) (printing), 95 W (ready)	
Requirements	Input voltage (auto ranging) 200-240 V two wires and PE; 50/60 Hz (±3 Hz); two power cords; 13 A max printer power cord; 9 A max curing power cord	
Certification		
Safety	IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC)	
Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC)	
Environmental	ENERGY STAR®: RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT Silver; OSHA; (E marking compliant; Meets AgBB criteria; French VOC A+; Greenguard Gold; UL Ecologo; ZDHC - Level 1	
Warranty	One-year limited hardware warranty	

Ordering information

Product

YOU23A	HP Latex 700 W Printer	
Accessories		
21V10A 7HR16A 7HR18A 7HR19A 7HR19A T7U73A	HP Latex 700/800 User Maintenance Kit HP Latex 700/800 Textile Kit Accessory HP Latex 700/800 In Collector Foams Kit HP Latex 700/800 Media Loading Accessory HP Latex 500/700/800 Wiper Roller	
Original HP printing supplies		
4UU93A 4UU94A	HP 836 White Latex Printhead HP 836 Optimizer Latex Printhead	

4UU93A 4UU94A 4UU96A 4UV29A 4UV25A	HP 836 White Latex Printhead HP 836 Optimizer Latex Printhead HP 836 Latex Maintenance Cartridge HP 832 1-liter White Latex Ink Cartridge HP 832 1-liter Black Latex Ink Cartridge
4UV76A	HP 832 1-liter Cyan Latex Ink Cartridge
4UV77A	HP 832 1-liter Magenta Latex Ink Cartridge
4UV78A	HP 832 1-liter Yellow Latex Ink Cartridge
4UV79A 4UV80A	HP 832 1-liter Light Cyan Latex Ink Cartridge HP 832 1-liter Light Magenta Latex Ink Cartridge
4UV80A 4UV81A	HP 832 1-liter Optimizer Latex Ink Cartridge
4UV82A	HP 832 1-liter Overcoat Latex Ink Cartridge
4UV83A	HP 832 Ink Mix Container
4UV95A	HP 836 Black/Cyan Latex Printhead
4UV96A 4UV97A	HP 836 Magenta/Yellow Latex Printhead HP 836 Light Cyan/Light Magenta Latex Printhead
4UV97A 4UV98A	HP 836 Overcoat Latex Printhead

Original HP large format printing materials

HP PVC-free Wallpaper (UL GREENGUARD GOLD Certified⁶, FSC[®] certified⁷, meets AgBB criteria⁸) HP Photo-realistic Poster Paper HP Premium Satin Canvas HP Prime Mate Air GP (REACH compliant⁹) HP Premium Removable Gloss Adhesive Vinyl (REACH compliant⁹)

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

U13DCE HP 2 year Next Business Day with Defective Media Retention U13DHE HP 3 year Next Business Day with Defective Media Retention U13DME HP 1 year Post Warranty Next Business Day with Defective Media Retention U13DSPE HP 2 year Post Warranty Next Business Day with Defective Media Retention

ECO highlights

- Inks do not use reactive monomer chemistry, are ozone-free, and meet the ZDHC standard¹ Can win new business with odorless prints, UL ECOLOGO®/UL GREENGUARD Gold Certified ink, and more² Eco-Carton replaces plastic cartridge with 80% reduction in plastic, achieves 66% (C2e reduction³ Zero landfill—local outer carton recycling, free take-back inner ink bag via HP Planet Partners⁴

Please recycle printing hardware and eligible printing supplies and prints. Find out how at our website: http://www.hp.com/ecosolutions

1 See http://www.roadmaptozero.com. Printing with HP Latex Inks avoids the problematic reactive monomers associated with UV printing. Acrylate monomers present in uncured UV inks and UV-gel inks can damage skin. There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print. For certifications, see http://www.uLcom/gel. and http://www.uLcom/ge. "Oze reduction based on moving from plastic ink cartridge to cardboard HP Eco-Carton ink cartridge, with annual manufacturing savings of 291 hons and transport savings of 8 tons. Equivalent to 1, 194,028 km (741,935 miles) driven by an average passenger vehicle or over 38 million smartphones charged. "The ink cartridge HP Eco-Carton outer carto is 100% recyclable through local cardboard/paper programs. Inner materials including the ink bag are 55% recyclable and can be returned free of charge to the HP Planet Partners program for reprocessing of plastic parts. Zero landfill. For take-back of ink bag/printhead/prints, visit http://www.hp.com/recycle to see how to participate and for HP Planet Partners program availability, program may not be available in your jurisdiction.

¹ Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects.
² The color variation between printed jobs has been measured at 12 pass mode on vinyl media following best practices for tiling layouts and within this limit: 95th percentile of pairwise color differences (95% of colors) = 1 dE2000. Reflective measurements on a 943 color target under CIE standard lluminant DS0, and according to the standard CIDE2000 as per CIE braft Standard DS 014-6/E2012. 5% of colors), and according to the standard CIDE2000 as per CIE braft Standard DS 014-6/E2012. 5% of colors may experience variations above 1 dE2000. Backlit substrates measured in transmission mode may yield different results.
³ Wiper roller is an optional accessory.
⁴ Automatic horizontal cutter is for use with thinner banners and canvas only. It is recommended to perform a test.
⁵ Textile R1A cessory required for long runs of textile and porous textile.
⁶ UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit http://www.uccom/gg or http://www.greenguard.org.
⁷ Trademark licens code F2C-C115319.
⁸ With PL Latex Inks, prints meet AgBB criteria for health-related evaluation of VOC emissions. See http://invelubundesamt.de/en/topics/health/commissions-working-groups/committee-for-health-related-evaluation-of-building.
⁹ This compute for anot and the processor (VIC for part endrate) with the DL Latex Inks, prints meet AgBB criteria for health-related evaluation of VIC emissions. See http://unvelubundesamt.de/en/topics/health/commissions-working-groups/committee-for-health-related-evaluation-of-building.
⁹ This compute for parts and the processor devalues for the sender of the sender of the sender of the processor devalues of the sender of the sender of the procession sender of the sender of the

III UD/initiation becaution to the initiation of the initiation of the end of the end



