

Technical Data Sheet TrueCanvas Giclée 65/35

TrueCanvas[™] Giclée 65/35 is an 11oz canvas composed of a 65 percent cotton and 35 percent polyester blend with an acrylic-gesso top coat. The gesso coating can be folded and stretched without cracking and provides a uniform low-glare finish. TrueCanvas Giclée 65/35 is free of heavy metals and designed to offer crisp detail and rich tonal range making it ideal for fine resolution art reproduction as well as various art décor applications. TrueCanvas Giclée 65/35 is available with both matte and gloss finishes and is compatible with solvent, Latex, and UV inks in sizes ranging from 54" to 80".

Material Details

CHARACTERISTICS		TrueCanvas Giclée 65/35				
Support Cloth		65% Cotton, 35% Polyester				
Type of Coating		Polymeric Resin, heavy metal free		Polymeric Resin, heavy metal free		
Total Weight		350	g/m²	10.5 oz		
Type/Finish		Glo	oss	Matte		
		<u>Value</u>	Tolerance	<u>Value</u>	Tolerance	
L,A,B Value	L	92.0	± 2.0	92.0	± 1.0	
	Α	2.5	± 1.0	1.5	± 1.0	
	В	-4.0	± 1.0	-2.0	± 1.0	
Whiteness		>95		>85		
Opacity (%)		>94		>94		
Caliper (mil)		21.5	± 2.0	22.0	± 2.0	
Gloss Level	at 60°	6	± 2.0	3.0	± 2.0	
GIUSS LEVEI	at 85°	8	± 2.0	2.8	± 2.0	
Acidity (PH)		Neutral (Acid Free) and Archival				

Applications

	Art Reprographic	Banner	Wall Murals	Fine Art	Art Décor	Backdrops
Applications	•		-			•

Ink Printability

-								
Solvent	Eco	UV	Latex	Screen	Dye	Dye Direct	Metric (m)	English (inches)
	Solvent			Printing	Transfer	Direct	Up to 2.03m	Up to 80"
							00102.0011	001000

Key: ■ - Excellent □ - Good

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. A weight variance of +1/-2 is acceptable. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

www.ultrafleXX.com Updated: 05/2013 Ultraflex Headquarters 1578 Sussex Turnpike, Building 4 Randolph, NJ 07869 P. 973-627-8608 F. 973-627-8506 Ultraflex Europe Ltd. Hardwick Rd Industrial Park Great Gransden Bedfordshire, England SG193BJ P. +44 1767 677100 F. +44 1767 677190

Ultraflex Mexico

Available Sizes

Avena 316-B Col. Granjas Mexico Mexico City, 08400 P. +52 5531-823-632 F. +52 5558-037-809

1313 boulevard Dagenais ouest, Laval (Québec) Canada H7L 5Z9 - 450.622.6066 / 866.622.6066 - info@mediatech.ca - www.mediatech.ca